

Product Comparison



Feature	flowIQ® 3100	flowIQ® 3200
Flow rate shown in display	-	+
Consumption profile	-	+
Hourly log	-	+
Remote reading	Support for: <ul style="list-style-type: none"> • Wireless M-Bus • Wired M-Bus • Sigfox • GEO Display 	Support for: <ul style="list-style-type: none"> • Wireless M-Bus • linkIQ® • Pulse output • flowIQ® Gateway
Intelligent alarms	<ul style="list-style-type: none"> • Leak • Burst • Tamper • Dry • Reverse flow 	<ul style="list-style-type: none"> • Leak • Burst • Tamper • Dry • Reverse flow • Low battery • Low temperature • High temperature • No consumption • Max flow exceeded [Q > Q₄]
Display update	32 s	20 s
Water ingress protection	IP68	IP68
Sizes	1.6 - 63 m ³ /h / DN15-DN80	6.3 - 160 m ³ /h / DN32-DN100
Start flow	2 l/hour	5 l/hour
Battery lifetime	Up to 16 years	Up to 20 years
MID approval	R630	R1000
Materials	Brass, stainless steel, glassfibre-reinforced composite	Stainless steel, glassfibre-reinforced composite
Can be delivered with extended product warranty	✓	✓
Can be delivered with sample testing of meter accuracy	✓	✓